



# ACTEK<sup>®</sup> MFG. & ENG. INC.

## LIFTING DEVICE SAFETY INFORMATION

Actek<sup>®</sup> Mfg. & Eng., Inc. products are intended for use only by trained, qualified and experienced workmen. Misuse of any Actek<sup>®</sup> product or lack of supervision and inspection can lead to serious accidents including death. Actek<sup>®</sup> Mfg. & Eng., Inc. has always stressed that safety is of utmost importance.

Prior to any use of Actek<sup>®</sup> product, evaluation of the product application, safety precautions, safe working load, and control of all field conditions is mandatory. Prevent applications that exceed the safe working load or any other product misuse. Actek<sup>®</sup> cautions you that all safety factors shown are approximate. Safe working loads should never be exceeded under any circumstances.

If you have any questions about the proper use or installation of any Actek<sup>®</sup> product, please contact our office directly.

1110 Fullerton Road - City of Industry, CA 91748 • (800) 752-7229

---

### Safety Notes

Actek<sup>®</sup> Mfg. & Eng. Inc. ensures that all materials used on all our products meets or exceeds the safety requirements for lifting. The safe working loads listed are based upon a new or in "as new" condition product. A safe working load is considered to be the greatest load that should be applied to an item at any time.

---

### Inspection & Maintenance

In order to insure the safest lifting, all for safety purposes, Actek<sup>®</sup> products must be properly used and maintained in the proper manner. Hoist rings may be are subject to wear, corrosion, deformation, overloading, and other limiting factors which may will affect the safe working load. Prior to use the user of any Actek<sup>®</sup> product, the product should be regularly inspected to determine if it may be used or whether it should removed from service. It is the responsibility of the user to inspect all lifting units for signs of wear and to discard the any parts when showing visible signs of wear. Every user should establish a safety inspection program for routine visual inspection of all products to determine whether signs of wear (e.g. cracks, corrosion, deformation) are present. The product inspection schedule should be established based upon factors such as frequency of use, period of use and environment. In addition to the regular safety inspection, the following safety directives must be followed:

- Prior to use, always inspect hoist rings for possible wear or damage. Never use hoist rings that show any sign of wear or damage.
- Never use hoist rings if bail is bent or elongated.
- Prior to use, threads must be clean, undamaged, and must fit properly.
- Always install hoist rings using the listed torque value. Periodically check torque because screws could loosen during extended service.
- Bent bolts should be discarded or replaced never straightened; failing to do so may lead to serious injuries or death.
- Never use washers or any spacers between bushing and mounting surface.
- Always make sure the hoist ring pivots and rotates in all directions freely.
- Never use hoist ring near or around corrosive material.
- If hoist ring is exposed to extreme temperatures (hot or cold), please contact our engineering department for suggestions/consultation.
- Safe working loads should never be exceeded under any circumstances.

If there are questions regarding the replacement or repair of worn Actek<sup>®</sup> products, please contact our engineering division.

1110 Fullerton Road - City of Industry, CA 91748

Toll Free: (800) 752-7229 Tel: (626) 581-3424 Fax: (626) 581-3423 Web: [www.actekmfg.com](http://www.actekmfg.com) Email: [sales@actekmfg.com](mailto:sales@actekmfg.com)